

Product Description

Single sided spun bonded polypropylene carrier coated with clear hotmelt synthetic rubber based adhesive.

Applications

Wall mending, designed for mending wall-cracks. Compatible with wallpaper and painting.

Features & Benefits

- Excellent tack
- Good adhesion
- Excellent crossways extension characteristics

Application notes

Apply with a firm pressure to clean, non-porous surfaces. Test an inconspicuous area before use to determine suitability

Technical Performance

Description	Units	Value	Test Method
Total thickness	Mic	90	Digital calliper
Peel adhesion to steel	N/mm	1200	-
Loop tack	N/mm	1000	-
Shear	Hrs @ 1 Kg	100	-
Temperature range	°c	-20 to 60	

Declaration of Conformity Information

REACH SVHC Status

NO SHVC present according to candidates list of the **UK 25/06/20 & EU 27/06/24**

RoHS 2&3 Compliance Status

EU 2015/863 amending Annex II to Directive **2011/65/EU** of the European Parliament and of the Council as regards the list of restricted substances

Storage Details

Store at the moderate temperature and humidity environment.

The information supplied is accurate to the best of Fosseways knowledge and is based upon all current data available to it. Properties quoted are typical and do not therefore constitute a specification. Customers must complete their own assessment of the product for its intended application under their own conditions. Our technical advice is to be regarded as an expression of opinion only and although such advice is given in good faith, it shall not, in any circumstances, be regarded as the basis of or as being a representation or statement of fact. This applies also where propriety or protective rights of third parties are involved. Any liability arising in respect of our products will be strictly limited to the value of those products charged to the customer and shall not extend to any consequential loss whatsoever and howsoever arising. This document does not form part of any contract with a customer (02/05/13)