NEC Approved Exhibition Carpet Tape

Product Infomation

Ref: 4109



1. Product Description

Rev 2023

Our 4109 is a double-sided self-adhesive tape with polythene stretchable carrier, differentiated adhesive:

- close side: clear, permanent synthetic rubber
- open side: clear removable acrylic

Main Applications

The 4109 is specifically designed for temporary carpet installations direct to exhibition hall floors. It is easily peeled off from carpet backing and exhibition venue floors.

We do not recommend using on marble or wooden floors, as well as floors that have been treated or varnished, as this may cause residual adhesive to remain on floor surface.

Features

Aggressive adhesive with high tack, high adhesion and high cohesion on the permanent side; high tack and very cohesive on the removable side.

2. Product Specification

Liner

80 g brown two sided silicone paper.

Carrier

Printed blue semi-transparent LDPE

Adhesive

Differentiated:

- Closed Side: clear, permanent synthetic rubber
- Open side: clear removable acrylic

3. Product Data

Elongation	%	280
Tensile Strength	N/cm	17
180° Peel	N/cm	Closed 14
		Open 2,5
Static Shear	h	Closed >120
		Open >220
Rolling Ball Tack	cm	Closed 2
		Open 5,5
Thickness	μ	145
Thickness Liner	μ	70
Performance Temperature	°C	Min -10°C
		Max +50°C

4. Packaging Specifications

Important Notice

All UKIT products are subjected to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects. Published information concerning UKIT products is based upon research, which the Company believes to be reliable, but some information does not constitute a warranty. Because of the variety of possible uses for UKIT products and continuing development of new uses, the purchaser should carefully consider the fitness and performance of the product for each intended use and the purchaser assumes all risks in connection with such use. Seller shall not be liable for damages in excess of the purchase price of the product nor for incidental nor consequential damages. All specifications are subject to change without prior notice.