

R571NP – Exhibition Grade Flooring and Carpet Tape

Double-sided Peel-Perm LDPE Tape

Technical Data

Description The tape is a printed white 60 micron low density polyethylene film carrier. It is coated on the open side with a low-tack peelable adhesive and on the closed side with a high-tack permanent adhesive, with an 80gsm differential white glassine release liner, which is sideways-tearable.

Construction	Carrier:	60µ printed white low density polyethylene
	Adhesive open side:	WM803 modified acrylic peelable
	Adhesive closed side:	WM1070 pure acrylic permanent
	Release liner:	80gsm two side siliconised white glassine 2:1
	Thickness (carrier & adh):	0.108mm
	Carrier Thickness:	0.060mm
	Adhesive colour:	Clear

Typical Application The tape is ideally suited for temporary carpet-laying, as at exhibitions.

Application The open side (i.e. that which is exposed as the tape is wound off the roll) is applied to the floor, which must be clean, and the release liner removed to expose the permanent adhesive on to which the underside of the carpet is firmly placed. The peelable side to the floor can therefore be removed without leaving residue.

Typical Physical Properties **These figures are average values and should not be regarded as maximum or minimum values for specification purposes.**

Peel Adhesion Steel (24 hours) FINAT FTM1	- OPEN	5 N/25mm
	- CLOSED	20 N/25mm
Initial Tack Steel FINAT FTM9	- OPEN	4 N/25mm
	- CLOSED	10 N/25mm
Static Shear (hrs @ 1kg) FINAT FTM8	- OPEN	0.7 hours
	- CLOSED	30 hours
Recommended temp. application range	-	5 to 25 °C
Shelf Life	-	12 months PSMA conditions

Warranties

All statements, technical information and recommendations about **Webmaster** products are based on tests believed to be reliable but do not constitute a guarantee or warranty. All products are sold on the basis that the purchaser shall make their own tests to determine the suitability of such products for their particular applications and uses, and that the purchaser assumes all risks and liabilities for the results of the use of the products, including use in accordance with the seller's recommendations. No salesman, representative or agent of **Webmaster** is authorised to give any guarantee, warranty or make any representation contrary to the above.